



**Miniature Fuses**  
Ceramic Tube

**F**

Size **6.3 x 32 mm**      Rated Voltage **600 V**      **Fast Acting**      Standard **Special Type**

Rated Current [A]	Part No.	Voltage Drop [mV]	Pre-arcing I <sup>2</sup> ts-value [A <sup>2</sup> s]	Rated Breaking Capacity [kA]	Power Dissipation [W]	Weight [kg/100]	Pack
0.200	70 094 63.0.200	6 500	0.0035	50	2.9	0.12	100
0.500	70 094 63.0.500	800	0.19	50	1.1	0.12	100
0.800	70 094 63.0.800	600	0.49	50	1.4	0.12	100
1	70 094 63.1	400	0.4	50	1.2	0.12	100
2	70 094 63.2	280	2.5	50	1.6	0.12	100
3	70 094 63.3	260	7.5	50	2.2	0.12	100
5	70 094 63.5	190	40	50	2.9	0.12	100
7	70 094 63.7	150	100	50	3.8	0.12	100
10	70 094 63.10	150	240	50	4.0	0.12	100

**Pre-Arcing Time Limits**

Rated Current	1.5 I <sub>n</sub>	2.1 I <sub>n</sub>	2.75 I <sub>n</sub>	4 I <sub>n</sub>	10 I <sub>n</sub>
200 mA	> 1 h	<30 min.	20 ms	8 ms	< 20 ms
800 mA			100 ms	400 ms	
1 A			1.5 s	20 ms	< 50 ms
10 A			5 s	1 s	

